

TECHNICAL DATA SHEET

Revision date: 01.07.2024

HOLLOW SECTION WAX IN CARTRIDGE

Article number:	37815
Colour:	transparent brown
Intended use:	Car refinishing product/ Protective coating
General characteristics:	Hollow section wax is a protective coating for preventing corrosion. It is based on special waxes which conserve and seal car body cavities. Thanks to its excellent penetrating properties, moisture is displaced even from small corners and seams. Due to its consistency the wax doesn't drip or run.

PAINTING PREPARATION PROCESS

Hardener: without hardener
Dilution: without thinner; ready to use

APPLICATION PROCESS

Before use, carefully read and observe the warning texts on the label!

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +12 °C and max. air humidity should not exceed 80%.

Application method	Pressure	Nozzle
UBS spray gun	4.0 - 6.0 bar	5.0 - 10.0 mm

Spraying operations	DFT	Consumption
1 - 2	-	-

■ Processing tips

- Please make sure the product has a temperature of at least 15 - 20 °C before the application.
- Shake well before use.

VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max. 448 g/l VOC

Shelf life:

36 months, if stored in tightly closed original containers

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:

info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.